

## YRT 370

### **BASIC INFORMATION**

PRODUCT GROUP: Non-woven products  
PRODUCT SUB-GROUP: Polyester membrane

#### MAIN APPLICATIONS:

- Pneumatic transport of cement and ash and other powdery

### **TECHNICAL INFORMATION**

QUALITY NUMBER: 0709021/032  
PRODUCER: Konus Konex d.o.o.  
**PRODUCT NUMER: 9905586**

| <b>No</b> | <b>CHARACTERISTIC</b>      | <b>Measure Unit</b>   | <b>VALUE</b> | <b>CONTROL METHOD</b> |
|-----------|----------------------------|-----------------------|--------------|-----------------------|
| 1         | area weight                | g/m <sup>2</sup>      | 3300 – 3500  | ISO 9073-1            |
| 2         | thickness                  | mm                    | 6.8 – 7.0    | ISO 4603-1            |
| 3         | tensile strength MD        | N/ 5 cm               | > 5000       | ISO 9073-3            |
| 4         | tensile strength CD        | N/ 5 cm               | > 4000       | ISO 9073-3            |
| 5         | elongation at break MD     | %                     | 15 – 20      | ISO 9073-3            |
| 6         | elongation at break CD     | %                     | 20 – 25      | ISO 9073-3            |
| 7         | air permeability at 200 Pa | l/dm <sup>2</sup> min | 15 – 25      | ISO 9237              |